

Reverse Engineering Organization and Topics

Hasso-Plattner-Institut Potsdam
Software Architecture Group
<http://www.hpi.uni-potsdam.de/swa/>


2018



Remember “Big Ball of Mud” SWT1?

“A **BIG BALL OF MUD** is haphazardly structured, sprawling, sloppy, duct-tape and bailing wire, spaghetti code jungle. We’ve all seen them. These systems show unmistakable signs of unregulated growth, and repeated, expedient repair. Information is shared promiscuously among distant elements of the system, often to the point where nearly all the important information becomes global or duplicated. The overall structure of the system may never have been well defined. If it was, it may have eroded beyond recognition. Programmers with a shred of architectural sensibility shun these quagmires. Only those who are unconcerned about architecture, and, perhaps, are comfortable with the inertia of the day-to-day chore of patching the holes in these failing dikes, are content to work on such systems.”


[Foote and Yoder 1997 Big Ball of Mud]



Lets do something about it...

Introduction: Reverse Engineering


- Find out how something works, in order to ...
- Change, extend, refactor, rebuild, use ...
- Self-supporting Development Environments
- Static vs. dynamic analysis




Development Environments



Lively Kernel, JavaScript,
WebComponents, D3





Squeak Smalltalk



TOPICS

Xray through UI



- Lively **XRay** tools overlay graphical user interface to:
 - Reveal and inspect structure of the DOM hierarchy
 - Make user events visible
- **Goal:** Extend XRay tools to **reveal behavior**
 - Trace and show **computation within components**
 - Link computation to dynamic DOM structure and static source code
 - Highlight **reactive components** and their over-time behavior

Scriptable Trace Viewer in Lively4



Stack Trace in Blink DevTools

- Stack traces provide **over-time view** on system execution
- Generic tracer available as part of Blink DevTools, however, no domain knowledge or high-level abstractions are incorporated into such views
- **Goal:** Implement a **scriptable trace viewer**
 - Annotate and enhance with **domain knowledge**
 - Compute on and **query traces**

Tracking JS Built-ins for Changes

```
person.fullname() // Foo Bar

aexpr(() => person.fullname())
  .onChange(console.log)

person.firstname = `Hello` // prints `Hello Bar`
person.lastname = `World` // prints `Hello World`
```

- Active Expressions track arbitrary JavaScript expressions for change
- Using source code transformation, we intercept get and set operations to object members, locals, and globals
- Certain JavaScript built-ins do not follow this pattern, thus, cannot be tracked for changes currently
`aexpr(() => input.value) ?`
- Some DOM elements change properties under the hood
- **Goal:** Reify changes to JavaScript Built-ins and DOM elements
 - Integrate those mechanisms into Active Expressions

Static Analysis for High-Level Language Features

graphics.js >> Rectangle

45

setWidth(width) {

46

this.width = width;

47

}

48

49

setHe

50

this.h

51

}

52

assignment may trigger 3 active expressions

Rectangle::constructor([...])

Rectangle::widthR([...])

View::resize([...])

12

this.width = width;

13

14

aexpr(::this.aspectRatio)


15

.onChange(::this.rescale);

16

- Static analysis models like **data dependency and call graphs** aid semantic code navigation
- Dynamic language features complicate graph generation
- **Goal:** Extend a static analyzer to incorporate **reactive programming concepts** (such as active expressions)

Why and Why Not Questions



- Identifying the root cause of a failure involves an enormous search space, often done manually
- The WhyLine automates this process, by allowing programmers to ask **why and why not questions** about a program execution
- Goal:** Implement a **WhyLine for JavaScript**

[1] Andrew J. Ko, and Brad A. Myers. "Designing the Whyline: A Debugging Interface for Asking Questions About Program Behavior" SIGCHI (2004), ACM.


[2] Andrew J. Ko, and Brad A. Myers. "Finding causes of program output with the Java Whyline" SIGCHI (2009), ACM.

Github Explorer

Search

Refine

Visualize




- GitHub as powerful data source for all kinds of software architecture and engineering questions
- **Goal:** Provide a tool to explore GitHub data in Lively4
 - Stream data for immediate feedback
 - User experience similar to the Lively Kernel World Explorer (explorable schemata, tangible results)

Stroposcoping for non-graphical Objects



Stroposcopic View on Game Entities [1]



Rendering Multivariate Data over Time [2]


- Stroposcopic views allow to comprehend the **over-time behavior** of objects, but are **limited to graphical objects**
- Challenge: Arbitrary objects are n-dimensional data points
- Hypothesis: Only few properties of an object change frequently
- **Goal:** Provide a stroposcopic view for arbitrary JavaScript objects

[1] Bret Victor - Inventing on Principle [<https://www.youtube.com/watch?v=PUv66718DII>]

[2] Gapminder [<https://www.gapminder.org/>]


Lively Object Converter

- Migrate older Lively Kernel Objects / Worlds (JavaScript / DOM)
- Object structure and behavior
- Compatibility layers (Context-oriented Programming)



Lively4 Semantic Code Overview


- Files vs. modules, classes, methods (JavaScript)
- Static and dynamic structure and dependencies
- Code coverage / system heat map



Exploring Even Large Databases

BSEG join BKPF join KNA1

KUNNR, MANDT, BUKRS, BELNR, GJAHR, WRBTR, SHKZG



- Working with legacy systems often involves understanding obscure data schemata
- Working in an with Smalltalk-style liveness eases the exploration process
- Large datasets would degrade the liveness
- Making use of streaming and sampling to enable a short feedback loop when working with lage data sets
- Algorithms and tools for characterizing the data and pointing out relevant aspects

“The Program according to Garp”

Diary of aCompiler(10293192)

```
-> aClassBrowser #compile: aText(201241923)
  <- aParser(12391029) #parse: aText(201241923)
    -> aParser(12391029) #instanceVariables
  <- anASTNode(95812092) #checkClassNames
  <- MethodCue #new
  <- aMethodCue(82934823) #ast: anASTNode(95812092)
```

- Who called me? Whom did I call? What did we exchange? In which context did we do that? What is my general role in the application?
- Tracing from the perspective of a single object
- Making the data accessible through a graphical tool allowing for browsing and querying
- Related work
 - Lienhard, Adrian, Stéphane Ducasse, and Tudor Gîrba. "Object flow analysis: taking an object-centric view on dynamic analysis." *Proceedings of the 2007 international conference on Dynamic languages: in conjunction with the 15th International Smalltalk Joint Conference 2007*. ACM, 2007.
 - Vasily Kirilichev, Eric Seckler, Benjamin Siegmund, Michael Perscheid, and Robert Hirschfeld. *Stepwise Back-in-time Debugging*. In Proceedings of GI Informatiktage 2014, Potsdam, Germany, March 27-28, 2014, GI.



Categorizing Message Categories

```
def set_color_space(self, color_space_name)
  self.color_space_name = color_space_name
```

Predicates

```
def is_srgb(self):
  return self.color_space_name == 'srgb'
```

```
((SystemNavigation default allImplementorsOf: #expectedFailures)
  collect: [:m | m category]) asSet
```

```
"Prints" #(accessing characterization failures
            running setup testing 'testing-outer' tests)
```



- Code sections or message categories are useful for navigating large classes
- What could be **useful metrics** for finding relevant/interesting/problematic message categories?
 - Size
 - Heterogeneity (in how many other categories are message from this category?)
 - ...
- How would an **automatic refactoring tool for categories** look like?
- Outlook: What if we had **tags instead of categories** which allowed us to browse the system from different angles?

Finding and Using Implied Protocols

```
max: aMagnitude
  ^ self > aMagnitude ifTrue: [self] ifFalse: [aMagnitude]

> aMagnitude
  ^ aMagnitude < self

between: min and: max
  min <= self ifFalse: [ ^ false ].
  ^ self <= max

<= aMagnitude
  ^ (self > aMagnitude) not


...
```



- Some protocols rely on a very small set of primitive messages
- In single-inheritance systems they can be difficult to
 - Recognize (#between:and: only requires #< and #=
 - Implement (a class supports #do: but not #collect:)
- How to automatically determine semantically coherent implied protocols?
- How to provide guidance in implementing an implied protocol in a domain class?

Polymetric Views

- Polymetric exploration tool in Squeak Smalltalk
- Software Visualization
- Packages, classes, methods + software metrics
- Integration with Smalltalk tools



Class	NOA	NOM	LOC
PasteUpMorph	13	487	3569
DialogWindow	15	83	575
HandMorph	25	153	1183



LOC	Method
56	handleEvent:
54	fullDrawOn:
52	generateMouseEvent:
46	updateCacheCanvas:
39	processEvents
36	generateDropFilesEvent:
31	grabMorph:from:
21	generateKeyboardEvent:
20	nonCachingFullDrawOn:




SSL Support in GraalSqueak

build passing coverage 64%


A [Squeak/Smalltalk](#) implementation for the [GraalVM](#).

- Reverse-engineer SSL implementation in Smalltalk
 - Build tools for visualizing/debugging SSL handshake
 - Goal:** Implement SSL plugin in Java for GraalSqueak




Jupyter Notebooks in Squeak/Smalltalk

- Notebooks in Squeak/Smalltalk
 - Load and save (export) notebook files
 - Notebook UI, support for object inspector and charts, ...
- Experiment with multi-language support in notebooks (Smalltalk, Ruby, Python, JavaScript, LLVM, ...)



Exploring Web Request Processing



- Web server configurations define the processing steps a web server uses at run-time
- There are little tools to inspect the actual run-time steps and how they process the incoming requests
- Missing hot-loading results in a long feedback loop
- Potential servers: nginx, Apache
- Inspiration: Erlang webmachine

Fixing Old Software Bugs

- Old software is available as binary only
- How to explore the bugs and capabilities of the system? Can we infer navigation, content, system state information?



WAT?

From raw dissassembly ...

>C:4772 c2 ef e1 f2 e4 a0 bc ad 00

```
.C:477b 4C 89 41 JMP $4189
.C:477e A5 48 LDA $48
.C:4780 C9 14 CMP #$14
.C:4782 F0 56 BEQ $47DA
.C:4784 C9 15 CMP #$15
.C:4786 F0 52 BEQ $47DA
.C:4788 20 21 08 JSR $0821
```

>C:478b c2 ef e1 f2 e4 a0 00

```
.C:4792 A5 48 LDA $48
.C:4794 C9 10 CMP #$10
.C:4796 F0 16 BEQ $47AE
.C:4798 C9 11 CMP #$11
.C:479a F0 17 BEQ $47AE
```

```
cmd_board:
    lda player_transport    ; This is $00, so we branch to @onfoot.
    cmp #$1f
    beq @onfoot
    jsr j_pimm
    .byte "Board <=", $00

    jmp print_cant
```

```
@onfoot:
    lda tile_under_player    ; If the player is next to a ladder going up
    cmp #$14                ; the current tile is $10.
    beq board_horse
```




to annotatable,
navigable code

<https://magervalp.github.io/2015/04/02/u4-dungeon-frigate.html>
<https://gist.github.com/robey/1bb6a99cd19e95c81979b1828ad70612>

Recovering Data

- New engines for old games
 - How do we recover the game data? What format is that in?
 - What does the binary tell us? Magic format bytes? Archives without headers? Run-length encoding? Endianness? Can we interactively explore, infer, and guide extraction?
- Example: Warcraft 1 DOS vs Mac version. Can we extract the dataset?
 - Drop the archive into a tool, start exploring subsets of the data, find the code, images, etc....



<https://blogs.msdn.microsoft.com/oldnewthing/20180706-00/?p=99185>

<https://github.com/Wargus/war1gus/issues/78>

<http://www.blizzardarchive.com/pub/index.php?id=war1>



Topics

- Xray through UI
- Scriptable Trace Viewer in Lively4
- Tracking JS Built-ins for Changes
- Static Analysis for High-Level Language Features
- Why and Why Not Questions
- Github Explorer
- Stroposcoping for non-graphical Objects
- Exploring Even Large Databases
- Lively Object Converter
- Lively4 Semantic Code Overview
- “The Program according to Garp”
- Categorizing Message Categories
- Finding and Using Implied Protocols
- Polymetric Views
- SSL Support in GraalSqueak
- Jupyter Notebooks in Squeak/Smalltalk
- Exploring Web Request Processing
- Fixing Old Software Bugs
- Recovering Data

Development Links



- Squeak
 - <https://squeak.org/>
 - <https://github.com/hpi-swa/vivide>



- Lively4:
 - <https://github.com/livelykernel/lively4-core>
 - <https://lively-kernel.org/lively4/lively4-core/start.html>

Hand-In Reference Sheet

- Presentation
 - Presentation (pdf)
 - Screencast (mp4, public)
- End of Semester (in zip, link or email)
 - Presentation and Screencast **again**
 - Abstract (txt)
 - Figure / Screenshot (png, 800x600)
 - Sourcecode (MIT License)
 - Data
 - (squeak image)
 - README.md
- **All hand-ins will be archived in a public repository**

Organization

- Course
 - Project-Seminar, 4 SWS, 2 students per group
- Presentations
 - Mid-term Presentation (Nov)
 - End-term Presentation (Jan, Feb)
- Grading
 - 6 ECTS graded credit points
 - Grade based on project work and presentation
- Important dates
 - Project topics on October 16th
 - Enrollment with preferred topic names **on or before October 21th**
 - Mail to stefan.lehmann@hpi.de and jens.lincke@hpi.de with **RE18** in subject
 - Topic assignment on October 23th
 - Presentation dates determined after topics are assigned

